

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION	
NFPA Rating: Health-2; Flammability-1; Reactivity-0; Special- Manufactured For: WAXIE Sanitary Supply Address: 9353 Waxie Way Address: San Diego, CA 92193-1036 Phone: 1-800-995-4466 Emergency Response Number: 1-800-255-3924	HMIS Rating: Health-2; Flammability-1; Reactivity-0; Personal Protection-B DOT Hazard Classification: ORM-D Identity (trade name as used on label): Bar-Top Furniture Polish MSDS Number: A00134 Revision: 11 Date Prepared: 09/10/01 Prepared By: AH/IB Information Calls: 858-292-8111
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA	

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
PETROLEUM DISTILLATES	68551-19-9	No	NE	NE	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS	
Boiling Point: N/A Vapor Pressure: PSIG @ 70°F (Aerosols): Max.55 Vapor Density (Air = 1): N/E Solubility in Water: Slight Appearance and Odor: Creamy white spray with lemon fragrance.	Specific Gravity (H2O=1): Concentrate Only = 0.954 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A Evaporation Rate (BuAc = 1): Slower Water Reactive: No

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA	
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.	Auto Ignition Temperature N/E FLAMMABILITY LIMITS in Air by % in Volume: % LEL: N/E % UEL: N/E EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.	

SECTION 4 - REACTIVITY HAZARD DATA	
STABILITY ☒ STABLE ☐ UNSTABLE Incompatibility (Mat. to avoid): Strong oxidizers and alkalis.	HAZARDOUS POLYMERIZATION ☐ WILL ☒ WILL NOT OCCUR Conditions to Avoid: Open flame, welding arcs, heat, sparks.
Hazardous Decomposition Products: CO2, CO, hydrogen chloride.	

SECTION 5 - HEALTH HAZARD DATA	
PRIMARY ROUTES OF ENTRY: ☒ INHALATION ☐ INGESTION ☒ SKIN ABSORPTION ☐ EYE ☐ NOT HAZARDOUS	
ACUTE EFFECTS:	
Inhalation: Excessive inhalation of vapors can be harmful and may cause headaches, dizziness, asphyxia, anesthetic effects and possible unconsciousness.	
Eye Contact: Mild irritant.	Skin Contact: Mild irritant.
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.	
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or lung damage.	
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, upper respiratory conditions, liver disease & heart irregularities.	

EMERGENCY FIRST AID PROCEDURES	
Eye Contact: Flush with water for at least 15 minutes. If irritated, seek medical attention.	
Skin Contact: Wash with soap and water. Remove contaminated clothing & launder before re-wearing. If irritated, seek medical attention.	
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.	
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.	

SECTION 6 - CONTROL AND PROTECTIVE MEASURES	
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.	
Protective Gloves: Latex if skin is easily irritated.	Eye Protection: Safety glasses recommended.
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.	
Other Protective Clothing & Equipment: None	
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.	

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE	
Steps To Be Taken If Material Is Spilled Or Released: Absorb spilled liquid with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH TO SEWER.	
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.	
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.	
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.	

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.
 ** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only